



Standard Printer TA200 SERIES



***TSC introduce latest value model,
easy to use TA200.***

The TA200 reinvents the definition of value for low cost desktop label printers. The price of the TA200 may be inexpensive, but it looks and performs better than its expensive competition. The TA200 features two durable gear-driven motors that are capable of handling large capacity 300 meter ribbons and large rolls of media inside its sleek design.

If the 5" interior label capacity is not enough, simply add an external media unwinder and the TA200 can easily handle 8.4" OD rolls of labels designed for expensive industrial label printers.

The print mechanism and ribbon handler of the TA200 is a modular design. The module may easily be removed from the printer for use in kiosk or print and apply applications.

The TA200 offers a low initial price, uses the most cost effective supplies available, and is built to last. These are virtually trouble free units. Once you plug it in, you won't have to worry about it.

The TA200 can print a wide variety of labels ranging from shipping labels to compliance and general purpose product identification labels and tags. Other applications include automobile service shops, walk-in shipping and mail centers, and inventory control for stock rooms.

TECHNICAL SPECIFICATIONS

	TA200	TA300
Technology	Thermal transfer / Direct thermal	
Print Head Type	Flat	
Resolution	203 dpi	300 dpi
Print Width	108 mm	104 mm
Print Length	Max 2794 mm	Max 1016 mm
Print Speed	Up to 102 mm (4 ips)	Up to 76 mm (3 ips)
Interface	USB2.0, Micro SD card slot.	
Barcodes	Code39, Code93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code11	
2D Codes	PDF-417, Maxicode, DataMatrix, QR code, Aztec, GS1 DataBar Composite Code	
Optional	RS-232C, Centronics, internal Ethernet interface (10/100 Mbps), External 802.11 b/g/n wireless, Bluetooth, peel-off module, cutter (full or partial cut), external roll mount, KP-200 Plus keyboard display unit, KU-007 Plus programmable smart key-board.	
External labels holder	Additional	
Dimensions	224 mm (W) x 186 mm (H) x 294 mm (D)	
Safety Regulations	FCC Class A, CE Class A, CCC, CB	