



Standard Printer TDP247 . TDP345



Fast economical printer performance in a small footprint

The TDP-247 series features two fast models. The TDP-247 printer is a 203 dpi resolution, 4" wide printer that prints at speeds up to 7 inches per second. The TDP-345 printer offers high resolution 300 dpi printing at speeds up to 5 inches per second. The easy to load center-biased clamshell design holds a large roll of labels and fits into areas other printers cannot and integrates easily into a wide range of applications. Simply open the cover and drop your labels into the printers. Top of form sensing by gap, black mark, or notch is standard and completely adjustable from side to side.

APPLICATIONS

- Small Office/Home Office Mailing
- Product Marking
- High Resolution Print & Graphics Applications
- File-Folder Labeling
- Retail Point-of-Sale
- Shelf Labeling
- Healthcare Specimen Labeling
- Inventory & Asset Management
- Shipping

TECHNICAL SPECIFICATIONS

	TDP247	TDP345
Technology	Direct thermal	
Print Head Type	Flat	
Resolution	203 dpi	300 dpi
Print Width	108 mm (4.25")	106 mm (4.17")
Print Length	Max. 2286 mm (90")	Max. 1016 mm (40")
Print Speed	178 mm (7")/second	127 mm (5")/second
Interface	USB 2.0, RS-232, Centronics.	
Barcodes	Code 39, Code 39C, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11, China Post.	
2D Codes	DataMatrix, PDF-417, Maxicode, QR Code, Aztec.	
Optional	Peel-off module, Guillotine cutter (full cut or partial cut), Bluetooth module (serial interface), External 802.11 b/g/n wireless module (serial interface), Internal Ethernet 10/100 Mbps, External roll mount, media OD. 214 mm (8.4") on a 1" or 3" core, 3" core label spindle, KP-200 Plus keyboard display unit, KU-007 Plus programmable smart keyboard.	
External labels holder	Additional	
Dimensions	200 mm (W) x 164 mm (H) x 240 mm (D)	
Safety Regulations	FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TÜV/Safety, CCC	